Fontus

Power and Control over 2-Conductors



Send power and full 2-way 485 communication from Janus over 2-conductor cable with the magic of Fontus.

Features

- · No Programming needed
- · Plug-n-Play
- · Full 2-way 485 Control
- 12v trigger for use with projectors
- Dry Contacts for use with any control systems
- IR input for use with included IR Receiver & Remote
- Phantom power only available when used with the correct cabling. (Please contact SI for help or to see if you have the correct cabling)
- Low Voltage Power Input Fontus can receive power via any 7v - 28v DC power
- · Connectors are compatible with all 485 shades / screens
- · Compatible with any 2 conductor wire (18awg or larger)
- · Available in White (default) and Black (via SI rip cord)













In The Box

1 Motor Control Kit

1 Fontus Codec | 1 IR Receiver & Remote

1 Motor Conversion Kit

2 Fontus Codecs | 1 Five conductor jumper

8 Motor Conversion Kit

16 Fontus Codecs | 8 Five conductor jumpers

All Fontus come with their corresponding mating connectors in both black and white.

Works with

- Janus
- · Nano, Zen and Veil
- Dry Contact & SDN Keypads / RF gateway
- Solo / pro 2, Any Motorized 485 screens & power panels
- · 3rd Party Control Systems
- 12v Trigger Projector

Optional Accesssories

Spike Kit | Duocoup Expansion Kit (2 motor) | Din Rail Bracket | Single Gang Decora Keypad

