

Solo 3 - 575/675 Flown Kit Bracket Installation Instructions



Please use this QR Code to access documents related to product and latest instructions.



Solo 3 - 575/675 Flown Kit

Thank you for purchasing an SI product. If you have any questions or need any assistance with your Solo 3 - 575/675, we would love to help you.

Technical Support: 512.832.6939 **Hours of Support:** 7:30am - 5pm CST

screeninnovations.com support@screeninnovations.com

CONTENTS

Initial Consideration	1
Parts in the Box	2
Installation	3 - 1
Warranty	12

INITIAL CONSIDERATIONS

Plan your installation. Determine the length of your cassette and the centerline of your viewing area to make sure that you can install the brackets 2"- 8" from the end of the cassette.


Standard kits come with 2 Solo 3 - 575/675 Flown Kit Bracket assemblies. Each bracket can hold 50 lbs safely. For screens over 100 lbs, a third bracket is required.

As ceiling materials vary, screws for fixing to ceiling are not included. For guidance on appropriate screw systems, please consult your nearby specialized dealer.

PARTS IN THE BOX

(2) Solo 3 Flown Kit 575/675 - Brackets







(4) Screws for brackets

4 Hex key






5 Steel Cable





Parts in the Box


INSTALLATION


- Determine the desired viewing area with vertical centerline of the projected viewing area.
- The Solo 3 Flown Kit Brackets must be installed 2"-8" from each end of the cassette. Measure the overall length of the cassette to determine the min. and max. horizontal spacing of the mounts. Mark the location of the desired location of the brackets.























WARRANTY

New SI products carry a standard 1- year warranty on parts and labor.

FCC INFORMATION

This device complies with Part 15 of the FCC Results. Operation is subject to the following two conditions:

- 1. This device may not cause harmful interference, and
- This device must accept any interference received, including that which may cause undesired operation.

NOTE: This equipment has been tested and found to comply with the limits for CLASS B digital device, pursuant to Part 15 of FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment.

⚠ Changes or modifications not expressly approved by the manufacturer could void the user's authority to operate the equipment.

Solo 3, the Solo wordmark, and the Screen Innovations logo are registered trademarks and the exclusive property of Screen Innovations.

Warranty 12



Screen Innovations 9715-B Burnet Rd, Suite 400 Austin, TX 78758 512.832.6939 www.screeninnovations.com